

NAME

CURLOPT_VERBOSE – set verbose mode on/off

SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_VERBOSE, long onoff);
```

DESCRIPTION

Set the *onoff* parameter to 1 to make the library display a lot of verbose information about its operations on this *handle*. Very useful for libcurl and/or protocol debugging and understanding. The verbose information will be sent to stderr, or the stream set with *CURLOPT_STDERR*(3).

You hardly ever want this set in production use, you will almost always want this when you debug/report problems.

To also get all the protocol data sent and received, consider using the *CURLOPT_DEBUGFUNCTION*(3).

DEFAULT

0, meaning disabled.

PROTOCOLS

All

EXAMPLE

```
CURL *curl = curl_easy_init();
if(curl) {
    curl_easy_setopt(curl, CURLOPT_URL, "http://example.com");

    /* ask libcurl to show us the verbose output */
    curl_easy_setopt(curl, CURLOPT_VERBOSE, 1L);

    /* Perform the request */
    curl_easy_perform(curl);
}
```

AVAILABILITY

Always

RETURN VALUE

Returns CURLE_OK

SEE ALSO

CURLOPT_STDERR(3), *CURLOPT_DEBUGFUNCTION*(3),